


Turmdrehkran

172 EC-B 8 Litronic®

HÜFFERMANN

Vermietung – Transport & Montage –
Service, Wartung & Ersatzteile

turmdrehkrane@hueffermann.com, www.hueffermann.com




EN 14439:2009 – C25

LIEBHERR



HÜFFERMANN
krandienst




^{a)} Turmstück oder Kletterturmstück / Tower section or climbing tower section / Élément de mât ou élément de mât télescopable / Elemento torre oppure elemento torre telescopabile / Tramo torre o tramo torre trepable / Segmento de torre ou segmento de torre para ascensão / Башенная секция или секция наращивания

^{b)} Turmstück 16 HC + Übergangsrahmen 16 HC 175 – 21 HC 290 TF-0044c / Tower section 16 HC + transition frame 16 HC 175 – 21 HC 290 TF-0044c / Élément de mât 16 HC + cadre de raccordement 16 HC 175 – 21 HC 290 TF-0044c / Elemento di torre 16 HC + Adattatore torre 16 HC 175 – 21 HC 290 TF-0044c / Tramo torre 16 HC + Marco de transición 16 HC 175 – 21 HC 290 TF-0044c / Segmento de torre 16 HC + Quadro de transição 16 HC 175 – 21 HC 290 TF-0044c / Башенная секция 16 HC + Переходная рама 16 HC 175 – 21 HC 290 TF-0044c


		172 EC-B 8																			
m	r	m/kg	m/kg																		
			16,0	18,0	22,0	24,4	26,9	30,0	32,5	35,0	37,5	40,0	42,5	45,0	47,5	50,0	52,5	55,0	57,5	60,0	62,5
62,5	(r=64,0)	2,6 – 16,5 8000	8000	7290	5850	5210	4660	4110	3740	3420	3150	2900	2690	2500	2330	2180	2040	1920	1800	1700	1600
60,0	(r=61,5)	2,6 – 17,9 8000	8000	7970	6400	5700	5110	4510	4110	3770	3470	3210	2980	2770	2590	2420	2270	2140	2010	1900	
57,5	(r=59,0)	2,6 – 17,8 8000	8000	7920	6360	5670	5080	4490	4090	3740	3450	3190	2960	2760	2570	2410	2260	2120	2000		
55,0	(r=56,5)	2,6 – 20,2 8000	8000	8000	7300	6520	5850	5170	4720	4330	4000	3710	3450	3210	3010	2820	2650	2500			
52,5	(r=54,0)	2,6 – 20,2 8000	8000	8000	7290	6510	5840	5170	4720	4330	3990	3700	3440	3210	3000	2820	2650				
50,0	(r=51,5)	2,6 – 21,5 8000	8000	8000	7820	6980	6270	5550	5070	4660	4300	3990	3710	3470	3250	3050					
47,5	(r=49,0)	2,6 – 21,5 8000	8000	8000	7820	6990	6270	5560	5080	4660	4310	3990	3720	3470	3250						
45,0	(r=46,5)	2,6 – 22,5 8000	8000	8000	8000	7320	6570	5820	5320	4890	4520	4200	3910	3650							
42,5	(r=44,0)	2,6 – 22,4 8000	8000	8000	8000	7310	6560	5820	5320	4890	4510	4190	3900								
40,0	(r=41,5)	2,6 – 23,0 8000	8000	8000	8000	7490	6730	5970	5450	5010	4630	4300									
37,5	(r=39,0)	2,6 – 23,0 8000	8000	8000	8000	7510	6750	5990	5470	5030	4650										
35,0	(r=36,5)	2,6 – 22,9 8000	8000	8000	8000	7470	6710	5950	5440	5000											
32,5	(r=34,0)	2,6 – 22,9 8000	8000	8000	8000	7480	6730	5960	5450												
30,0	(r=31,5)	2,6 – 22,9 8000	8000	8000	8000	7470	6710	5950													
26,9	(r=28,4)	2,6 – 22,9 8000	8000	8000	8000	7460	6700														
24,4	(r=25,9)	2,6 – 22,9 8000	8000	8000	8000	7450															

LM 1



														172 EC-B 8 Litronic®							
m	r	m/kg	m/kg																		
			16,0	19,0	22,0	25,0	28,0	31,0	34,0	37,0	40,0	42,5	45,0	47,5	50,0	52,5	55,0	57,5	60,0	62,5	
62,5	(r=64,0)	2,6 – 18,0 8000	8000	7530	6410	5560	4890	4350	3910	3530	3220	2990	2780	2600	2430	2280	2140	2020	1910	1800	
60,0	(r=61,5)	2,6 – 19,3 8000	8000	8000	6940	6030	5310	4730	4250	3850	3510	3260	3040	2840	2660	2500	2360	2220	2100		
57,5	(r=59,0)	2,6 – 19,2 8000	8000	8000	6880	5980	5260	4690	4210	3810	3480	3230	3010	2810	2640	2480	2330	2200			
55,0	(r=56,5)	2,6 – 21,5 8000	8000	8000	7800	6780	5980	5340	4810	4360	3980	3700	3460	3240	3040	2860	2700				
52,5	(r=54,0)	2,6 – 21,4 8000	8000	8000	7770	6760	5960	5320	4790	4340	3960	3690	3440	3230	3030	2850					
50,0	(r=51,5)	2,6 – 23,0 8000	8000	8000	8000	7300	6440	5750	5190	4710	4300	4010	3750	3510	3300						
47,5	(r=49,0)	2,6 – 22,9 8000	8000	8000	8000	7280	6420	5740	5170	4690	4290	4000	3730	3500							
45,0	(r=46,5)	2,6 – 23,8 8000	8000	8000	8000	7570	6690	5980	5390	4900	4480	4170	3900								
42,5	(r=44,0)	2,6 – 23,7 8000	8000	8000	8000	7540	6660	5950	5360	4870	4450	4150									
40,0	(r=41,5)	2,6 – 24,3 8000	8000	8000	8000	7770	6870	6140	5540	5030	4600										

LM2















LM2 = Abweichende Geschwindigkeiten und Betriebsbedingungen./Variant speeds and service conditions./Vitesses et conditions de fonctionnement différentes./
Differenti velocità e condizioni di funzionamento./Otras velocidades y características de funcionamiento./Outras velocidades e características de funcionamento./
Нестандартные скорости и условия эксплуатации.

Hubhöhe

Hoisting height/Hauteur sous crochet/Altezza di sollevamento/
Altura bajo gancho/Altura de montagem/Высота подъема

16 HC 175							
	C 25						
11	42,3 [°]	41,8 [°]	–	–	38,0 [°]	–	–
10	39,8 [°]	39,3 [°]	–	49,3 [°]	35,5 [°]	45,5 [°]	46,9 [°]
9	37,3	36,8	–	46,8 [°]	33,0	43,0 [°]	44,4 [°]
8	34,8	34,3	44,8 [°]	44,3	30,5	40,5	41,9
7	32,3	31,8	42,3 [°]	41,8	28,0	38,0	39,4
6	29,8	29,3	39,8	39,3	25,5	35,5	36,9
5	27,3	26,8	37,3	36,8	23,0	33,0	34,4
4	24,8	24,3	34,8	34,3	20,5	30,5	31,9
3	22,3	21,8	32,3	31,8	18,0	28,0	29,4
2	19,8	19,3	29,8	29,3	15,5	25,5	26,9
1	17,3	16,8	27,3	26,8	13,0	23,0	24,4
0	14,8	14,3	24,8	24,3	10,5	20,5	21,9
	m	m	m	m	m	m	m
	16 HC 175 UC-0460m	16 HC 175 UC-0460m	16 HC 175 UC-0460mr	16 HC 175 UC-0460mr	16 HC 175 FAR	16 HC 175 FAR	16 HC 175 CB-0460r

3,9 m	3,90 m + 5,85 m		16 EC 160/240			
13				52,5 ¹⁾¹⁾²⁾		53,7 ¹⁾¹⁾²⁾
12	11 + 1			50,6 ¹⁾¹⁾²⁾		51,7 ¹⁾¹⁾²⁾
11	10 + 1			48,7 ¹⁾¹⁾³⁾		49,8 ¹⁾¹⁾³⁾
10	9 + 1			46,7 ¹⁾¹⁾⁴⁾		47,8 ¹⁾¹⁾⁴⁾
9	8 + 1			44,8 ¹⁾¹⁾⁵⁾		45,9 ¹⁾¹⁾⁵⁾
8	7 + 1			42,8 ¹⁾¹⁾⁶⁾		43,9 ¹⁾¹⁾⁶⁾
7	6 + 1			40,8 ¹⁾¹⁾⁶⁾		42,0 ¹⁾¹⁾⁶⁾
6	5 + 1			38,9 ¹⁾¹⁾⁷⁾		40,0 ¹⁾¹⁾⁷⁾
5	4 + 1			37,0 ¹⁾¹⁾		38,1 ¹⁾¹⁾
4	3 + 1			35,0 ¹⁾	35,9 ¹⁾	36,1 ¹⁾
3	2 + 1			33,0 ¹⁾	33,9 ¹⁾	34,2 ¹⁾
2	1 + 1			31,1	32,0	32,2
1	0 + 1			29,2	30,0	30,3
0				27,2	28,1	28,4
				25,3	26,1	26,5
				23,3	24,2	24,6
				21,4	22,2	22,7
				19,4	20,3	20,8
				17,5	18,3	18,9
				15,5	16,4	17,0
				13,6	14,4	15,1
				11,6	12,5	13,2
				9,7	10,5	11,3
				7,7	8,6	9,4
				5,8	6,6	7,5
				3,8	4,7	5,6
			m	m	m	m
						
			16 EC 160 FA	20 EC 300 FA	16 EC 160 CB-0380m	20 EC 300 CB-0450m

		17 HC 200				21 HC 290			
12	-	-	-	-	63,1 ¹⁾	-	-	-	-
11	-	-	-	-	59,0 ¹⁾	-	-	-	-
10	-	-	-	-	54,8	71,4 ¹⁾	-	-	66,5 ⁹⁾
9	49,1 ¹⁾	-	-	-	50,7	67,2	59,5 ¹⁾	62,4 ¹⁾	58,2 ¹⁾
8	44,9 ¹⁾	54,5 ¹⁾	-	56,0 ⁸⁾	46,5	63,1	55,4	54,1	51,2
7	40,8	50,4 ¹⁾	44,8 ¹⁾	51,8 ¹⁾	42,4	59,0	51,2	49,9	47,1
6	36,6	46,2	40,7 ¹⁾	47,7	38,3	54,8	47,1	45,8	43,0
5	32,5	42,1	36,5	43,5	34,1	50,7	43,0	41,7	38,8
4	28,4	38,0	32,4	39,4	30,0	46,5	38,8	37,5	34,7
3	24,2	33,8	28,3	35,3	25,8	42,4	34,7	33,4	30,5
2	20,1	29,7	24,1	31,1	21,7	40,7	30,5	29,2	26,4
1	15,9	25,5	20,0	27,0	17,6	38,3	26,4	25,1	22,3
0	11,8	21,4	15,8	22,8	13,4	34,1	18,1	21,0	18,1
	m	m	m	m	m	m	m	m	m
									
	21 HC 290 Far	21 HC 290 Far	17 HC 200 UC-0460r	21 HC 290 CB-0450	21 HC 290 Far	21 HC 290 Far	21 HC 290 UC-0600	21 HC 290 UC-0800	








- 1) 1 x 16 EC 160 – 16 EC 240 TST-0390c
2) 6 x 16 EC 240 TS-0390c
3) 5 x 16 EC 240 TS-0390c
4) 4 x 16 EC 240 TS-0390c
5) 3 x 16 EC 240 TS-0390c
6) 2 x 16 EC 240 TS-0390c
7) 1 x 16 EC 240 TS-0390c

- 8) Ohne Klettereinrichtung / Without climbing equipment / Sans équipement de télescopage / Senza dispositivo di telescopaggio / Sin equipo de trepado / Sem mecanismo de telescopagem / Без обоймы наращивания
9) Ohne Fahrwerke / Without Travel Gear / Sans boogie / Senza dispositivi di traslazione / Sin cajas de traslación / Sem mecanismo de translação / Без механизмов передвижения

r = verstärkt / reinforced / renforcé / rinforzato / reforzado / reforçado / усиленный

Weitere Hubhöhen, Auslegerlängen sowie Klettern im Gebäude auf Anfrage. / Further hoist heights and jib lengths as well as climbing inside the building on request. / Autres hauteurs sous crochet et longueurs de flèche ainsi que hissage dans le bâtiment sur demande. / Ulteriori altezze gancio, lunghezze braccio così come telescopaggio all'interno dell'edificio su richiesta. / Para alturas bajo gancho superiores, otros alcances y trepado en el interior del edificio, consultar. / Outras alturas de elevação, comprimentos de lança e subida no edifício: sob consulta. / Другие высоты подъема, длины стрелы и самоподъем в здании – по запросу.








	U/min 0 ↔ 0,8 sl./min tr./min	7,5 kW FU
	0 ↔ 100,0 m/min	5,5 kW FU
	25,0 m/min	2 x 4,0 kW (16 HC 175) 2 x 5,5 kW (17 HC 200) 2 x 7,5 kW (21 HC 290)
 kVA		
24 kW FU		45 kW FU
35,0		54,0

kVA reduzierbar bei zu geringer Netz-Anschlussleistung, siehe BAL. /

kVA can be reduced in case of too little power of the mains, see instruction manual. /
kVA peut être réduit en cas de trop faible puissance du réseau, voir manuel d'instruction. /
kVA riducibili in caso di potenza di rete ridotta (si veda manuale uso e manutenzione) /
kVA variable para potencia de red demasiado pequeña, ver Manual de instrucciones. /
kVA reduzível no caso de capacidade da rede elétrica muito baixa, ver manual de
instruções. / Количество кВА может быть сокращено до минимальной общей
потребляемой мощности, см. инструкцию по эксплуатации.

¹⁰⁾ **Weitere Hublastdaten: siehe Betriebsanleitung. /** Further hoist load data:
see instruction manual. / Autres données de la charge de levage : voir manuel
d'instruction. / Altri dati sui carichi sollevati: consultare il manuale d'istruzione. /
Alturas bajo granco superiores según manual. / Outras tabelas de carga:
consultar manual de instruções. / Другие данные по весу поднимаемых грузов:
см. инструкцию по эксплуатации.

Montagegewichte: siehe Betriebsanleitung./Erection weights: see instruction manual./Poids de montage: voir manuel de service./Pesi di montaggio: vedere manuale d'uso./
Peso para el montaje: según manual./Pesos de montagem: veja-se as instruções p. uso./Масса монтируемых частей: см. инструкцию по эксплуатации.

Kranoberteil			Upper part of crane/Partie supérieure de grue/Parte superiore della gru/ Parte superior grúa/Parte superior do guindaste/Верхняя часть крана			L (m)	B (m)	H (m)	kg ⁽¹⁾
Pos. Item Rep Voce Pos. Ref. Поз.	Anz. Qty. Qte. Qta. Cant. Cant. Кол-во								
1a	1	Drehbühne mit Podesten /Slewing platform with plat- forms /Plate-forme tournante avec plates-formes /Piatta- forma girevole con pedana /Plataforma giratoria con plata- forma /Plataforma giratória com plataforma /Поворотная платформа с площадками			16 EC 160 16 HC 175 17 HC 200	5,52 5,52 5,52	3,32 2,32 2,32	2,80 2,52 2,52	7780 7750 7780
1b	1	Drehbühne /Slewing platform /Ensemble mât-cabine/ Piattaforma girevole /Conjunto plataforma de giro / Plataforma giratória /Поворотная платформа			16 EC 160 16 HC 175 17 HC 200	2,63 2,63 2,63	2,28 2,28 2,28	2,15 1,85 1,85	4850 4820 4850
1c	1	Klappspitze /Folding jib head /Pointe de flèche pliante / Punta ribaltabile /Pluma /Ponta da lança dobrável / Откидной кронштейн				1,92	1,40	1,92	930
1d	1	Kabine /Cabin /Cabine /Cabina / Cabina /Cabina /Кабина				2,31	1,94	2,41	1000
1e	1	Schaltschrank /Switch cabinet /Armoire électrique / Quadro elettrico /Armario eléctrico /Armário elétrico / Электрошкаф				2,31	2,02	1,95	1000
2.1	1	Gegenausleger /Counter-jib /Contre-flèche / Controfreccia /Contrapluma /Contra-lança / Консоль противовеса				13,50	2,30	1,54	6700
2.2	1	Gegenausleger, teilbar /Counter-jib, dividable /Contre-flèche, divisible /Controfreccia, divisibile /Contrapluma, divisible / Contra lança modular /Консоль противовеса, составная				11,74	2,27	2,44	6950
3	1	Ausleger-Anlenkstück mit Laufkatze und Lasthaken /Jib pivoting section with trolley and load hook /Pied de flèche avec chariot et crochet de levage /Elemento articolato bracciocon carrello e gancio /Pluma tramo primero con carrito y polipasto / Segmento base da lança com carrinho e gancho de carga / Корневая секция стрелы с тележкой и грузовым крюком				11,95	1,51	2,50	① 3700
4	1	Ausleger-Zwischenstück /Intermediate jib section / Elément intermédiaire de flèche /Sezione intermedia braccio /Tramo intermedio pluma /Peça suplementar da lança /Промежуточная секция стрелы				5,84	1,20	2,28	② 915
5	1	Ausleger-Zwischenstück /Intermediate jib section / Elément intermédiaire de flèche /Sezione intermedia braccio /Tramo intermedio pluma /Peça suplementar da lança /Промежуточная секция стрелы				11,92	1,20	2,28	③ 1580
6	1	Ausleger-Zwischenstück /Intermediate jib section / Elément intermédiaire de flèche /Sezione intermedia braccio /Tramo intermedio pluma /Peça suplementar da lança /Промежуточная секция стрелы				2,72	1,20	1,69	⑤ 355
7	1	Ausleger-Zwischenstück /Intermediate jib section / Elément intermédiaire de flèche /Sezione intermedia braccio /Tramo intermedio pluma /Peça suplementar da lança /Промежуточная секция стрелы				5,21 10,20 10,20 5,17	1,20 1,20 1,20 1,20	1,69 1,69 1,69 1,69	④ 590 ⑥ 920 ⑦ 625 ⑧ 300
8	1	Ausleger-Kopfstück /Jib head section /Pointe de flèche / Punta braccio /Tramo punta de pluma /Cabeça de lança / Концевая секция стрелы				1,48	1,39	1,86	⑨ 160
Turm			Tower / Mât / Torre / Torre / Torre / Башня						
9	11 9 12	Turmstück /Tower section /Elément de mât /Elemento di torre /Tramo torre /Torre /Башенная секция			16 EC 160 TS-0390c 16 EC 160 TS-0585 16 EC 160/240 TST-0390c 16 EC 240 TS-0390c 16 EC 240 TS-0585 16 HC 175 TS-0250c 16 HC 175 TS-0500c 17 HC 200 TS-0414c 21 HC 290 TS-0414c	4,19 6,14 4,21 4,21 6,16 2,50 5,00 4,14 4,14	1,60 1,60 1,60 1,60 1,60 1,80 1,80 1,90 2,30	1,72 1,60 1,72 1,72 1,60 1,80 1,80 1,90 2,30	1530 2030 2130 2120 2850 1200 2000 1940 2500
10	5 2	Turmstück lang /Long tower section /Elément de mât long /Elemento di torre, lungo /Tramo de torre largo /Peça de torre, comprida /Башенная секция, длинная			16 EC 160 TS-1170 16 HC 175 TS-1000c 16 HC 175 TS-1250c 17 HC 200 TS-1242c 21 HC 290 TS-1242c	11,99 10,00 12,50 12,42 12,42	1,60 1,80 1,80 1,90 2,30	1,60 1,80 1,80 1,90 2,30	3730 3700 4600 4900 6100
11	1	Grundturmstück /Base tower section /Mât de base / Elemento di torre base /Tramo base /Peça de base de torre / Секция основания			16 HC 175 TSB-1000c 16 HC 175 TSB-1000r 17 HC 200 TSB-0960 17 HC 200 TSB-0960r 21 HC 290 TSB-1242c 21 HC 290 TSB-1242r	10,00 10,00 9,60 9,60 12,42 12,42	1,80 1,80 1,90 1,90 2,30 2,30	1,80 1,80 1,90 1,90 2,30 2,30	4330 4200 4580 5450 8200 8100
12	1	Kletterturmstück /Climbing tower section /Elément de hissage de mât /Elemento torre di telescopaggio /Tramo de trepado /Tramo de telescopagem /Секция самоподъема			16 EC 160 ECTS-0390 16 HC 175 ECTS-0250 17 HC 200 ECTS-0414	4,19 2,75 4,30	2,13 2,20 2,30	2,11 2,45 2,45	1770 1460 2300

Pos.	Anz.	Item	Qty.	Rep	Qte.	Voce	Qta.	Pos.	Cant.	Ref.	Cant.	Pos.	Кол-во		L (m)	B (m)	H (m)	kg ⁽¹⁾
Klettereinrichtung																		
Climbing equipment/Equipement de télescage/Attrezzatura per allungamento della gru/ Equipo de trepado/Acessórios p. subida no edifício/Обойма наращивания																		
13	1	Führungsstück kpl./Guide section cpl./ Cage télescopique cpl. / Gabbia di sopraelevazione compl./ Torre de montaje completa/ Peça de guia compl./ Направляющая секция в сб.																

() Angaben in Klammern gelten für 16 HC 175 UC-0460mr, 21 HC 290 UC-0800. / The data in brackets are valid for an undercarriage of 16 HC 175 UC-0460mr, 21 HC 290 UC-0800. / Les données techniques indiquées entre parenthèses sont valables pour un châssis de 16 HC 175 UC-0460mr, 21 HC 290 UC-0800. / Caratteristiche in (...) valgono per carro di 16 HC 175 UC-0460mr, 21 HC 290 UC-0800. / Los datos entre paréntesis son válidos para carro de 16 HC 175 UC-0460mr, 21 HC 290 UC-0800. / Características em (...) válidas pelo chassis de 16 HC 175 UC-0460mr, 21 HC 290 UC-0800. / Данные в скобках относятся к 16 HC 175 UC-0460mr, 21 HC 290 UC-0800 опорной раме.

⁽¹⁾ Einzelgewichte / Single weights / Poids individuels / Singoli pesi / Tramo punta de pluma / Pesos de peças componentes / Индивидуальный вес

Änderungen vorbehalten! / Subject to technical modifications! /
Sous réserves de modifications ! / Con riserva di modifiche! /
¡Sujeto a modificaciones sin previo aviso! / Sujeto a modificações! /
С правом внесения изменений!

Sämtliche Angaben erfolgen ohne Gewähr. / This information is supplied without liability. /
Ces renseignements sont sans garantie. / Tutte le indicazioni fornite senza garanzia. /
Declinamos toda responsabilidad derivada de la información proporcionada. / Declinamos
qualquer responsabilidade quanto à informação fornecida. / Все данные указаны без обязательств.

TCS-001859-LBC-01 • EN 14439:2009 – A3 • BGL C.0.10.0160 • 04.19

Printed in Germany.

Hüffermann Krandienst GmbH

Ahlhorner Straße 89, 27793 Wildeshausen
Telefon: +49 4431 94555-0

turmdrehkrane@hueffermann.com
www.hueffermann.com